

PRODUCT-DETAILS

# SPB32/10M

## STEEL/PVC/BRAID COND NC32 10M



### General Information

Extended Product Type	SPB32/10M
Product ID	7TCA296040R0146
EAN	5020963005213
Catalog Description	STEEL/PVC/BRAID COND NC32 10M
Long Description	Highly Flexible Steel Conduit, Nominal Conduit Size 32mm, Outer Diameter 34.0mm, Inner Diameter 28.1mm, Maximum Bend Radius 60mm, Reel Length 10 Meters, Galvanised Steel Core with PVC Jacket and Galvanised Steel Overbraid

### Ordering

EAN	5020963005213
-----	---------------

### Dimensions

Product Net Depth / Length	10 m
Product Net Weight	13.56 lb 6.15 kg

### Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

---

### Additional Information

Application	Indoors / Outdoors - Enhanced EMI Screen - High Abrasion Resistance
Brand / Label	Adaptaflex
Flexibility	High
Material	Galvanized Steel Core and Overbraid with PVC Jacket
Nominal Size	1 in
Number of Batteries	0
Product Name	flexible metal conduit
Product Type	High Flexibility Conduit
Radius	60 mm
Special Functions	Very High UV Protection
UPC	786210245317

---

### Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPB32/10M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPB32/10M

---

### Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

---

### Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

