

PRODUCT-DETAILS

SPB50/10M

STEEL/PVC/BRAID COND NC50 10M



General Information

Extended Product Type	SPB50/10M
Product ID	7TCA296040R0161
EAN	5020963006289
Catalog Description	STEEL/PVC/BRAID COND NC50 10M
Long Description	Highly Flexible Steel Conduit, Nominal Conduit Size 50mm, Outer Diameter 56.0mm, Inner Diameter 48.4mm, Maximum Bend Radius 90mm, Reel Length 10 Meters, Galvanised Steel Core with PVC Jacket and Galvanised Steel Overbraid

Ordering

EAN	5020963006289
-----	---------------

Dimensions

Product Net Depth / Length	10 m
Product Net Weight	33 lb 14.966 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Indoors / Outdoors - Enhanced EMI Screen - High Abrasion Resistance
Brand / Label	Adaptaflex
Flexibility	High
Material	Galvanized Steel Core and Overbraid with PVC Jacket
Nominal Size	1-1/2 in
Number of Batteries	0
Product Name	ADAPTAFLEX
Product Type	High Flexibility Conduit
Radius	90 mm
Special Functions	Very High UV Protection
UPC	786210274706

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPB50/10M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPB50/10M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

