

25 mm

1 in

PRODUCT-DETAILS

Package Level 2 Depth /

B/M16-M12/RBRASS REDUCER M16 TO M12



| General Information | |
|------------------------|--|
| Extended Product Type | B/M16-M12/F |
| Product ID | 7TCA296050R0103 |
| EAN | 5020963031847 |
| Catalog Description | BRASS REDUCER M16 TO M12 |
| Long Description | 3/8 Inch Nickel Plated Brass Reducer, M16 to M12 |
| Ordering | |
| EAN | 5020963031847 |
| Dimensions | |
| Product Net Weight | .03 lb |
| | 13.605 g |
| Container Information | |
| Package Level 2 Units | 10 piece |
| Package Level 2 Width | 1 in 25 mm |
| Package Level 2 Height | 1 in |

Length 25 mm

| Additional Information | | |
|------------------------|--|--|
| Application | To Reduce Thread Sizes Between Pieces of Conduit | |
| Brand / Label | Adaptaflex | |
| Material | Nickel Plated Brass | |
| Nominal Size | M16 to M12 | |
| Number of Batteries | 0 | |
| Product Name | brass fitting for conduit | |
| Product Type | Reducer | |
| Special Functions | Designed to Help Maintain System Integrity | |
| UPC | 786210284170 | |

| Certificates and Declarations (Document Number) | |
|---|-----------------|
| Data Sheet, Technical Information | B/M16-M12/R |
| Declaration of Conformity - CE | 9AKK107492A9618 |
| Instructions and Manuals | B/M16-M12/R |

| Classifications | | |
|---------------------------------------|--------------------------------------|--|
| ETIM 6 | EC000938 - Enlargement/reducing ring | |
| ETIM 7 | EC000938 - Enlargement/reducing ring | |
| UNSPSC | 39131707 | |
| WEEE Category | Product Not in WEEE Scope | |
| IDEA Granular Category Code (IGCC) | 5548 >> Electrical conduit coupling | |

Categories

 $Low\ Voltage\ Products\ and\ Systems\ \rightarrow\ Installation\ Products\ \rightarrow\ Cable\ Protection,\ Explosion\ Proof\ and\ Lighting\ \rightarrow\ Flexible\ Cable\ Protection\ Systems$

