

PRODUCT-DETAILS

CPCMTC34/BL/50M

T/C BRD CPCM34 50M REELS



Product image
not available

General Information

Extended Product Type	CPCMTC34/BL/50M
Product ID	7TCA296100R0002
EAN	5020963020964
Catalog Description	T/C BRD CPCM34 50M REELS
Long Description	Medium Weight Conduit with Tinned Copper Braid, Nominal Conduit Size 34mm, NW Conduit Size 29, Coarse Conduit Pitch, Outside Diameter 34.5mm, Inside Diameter 27.2mm, Static Bend Radius 55mm, Reel Length 50 Meters, Polyester, Black

Ordering

EAN	5020963020964
-----	---------------

Dimensions

Product Net Depth / Length	50 m
Product Net Weight	129.25 lb 58.617 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Indoors / Outdoors, Low Temperature Flexing, High Impact Resistance
Brand / Label	Adaptaflex
Color	Black
Flexibility	Very High
Inside Diameter	27.2 mm
Material	Polyester
Nominal Size	34 mm
Number of Batteries	0
Outside Diameter	34.5 mm
Product Name	ADAPTAFLEX
Product Type	Medium Weight Conduit with Coarse Pitch and Tinned Copper Braid
Radius	55 mm
Special Functions	Very High UV Protection and Fatigue Life
UPC	786210273549

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	CPCMTC34/BL/50M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	CPCMTC34/BL/50M

Classifications

ETIM 6	EC001175 - Corrugated plastic hose
ETIM 7	EC001175 - Corrugated plastic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems



Product image
not available