

PRODUCT-DETAILS

LFH-SPSS20/25M

SS OVERBRAID LFH-SP COND NC20 25M



General Information

Extended Product Type	LFH-SPSS20/25M
Product ID	7TCA296100R0020
EAN	5020963050435
Catalog Description	SS OVERBRAID LFH-SP COND NC20 25M
Long Description	Low Fire Hazard, Medium Flexibility Conduit with Stainless Steel Overbraid, Nominal Conduit Size 20mm, Outside Diameter 21.5mm, Inside Diameter 16.9mm, Static Bend Radius 80mm, Galvanised Steel Core with Low Fire Hazard Jacket, Reel Length 25 Meters, Black

Ordering

EAN	5020963050435
-----	---------------

Dimensions

Product Net Depth / Length	25 m
Product Net Weight	16.87 lb 7.651 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in

	25 mm
Package Level 2 Height	1 in
	25 mm
Package Level 2 Depth / Length	1 in
	25 mm

Additional Information

Application	Rail, Buildings - Where Low Smoke & Toxicity is a Primary Concern
Brand / Label	Adaptaflex
Color	Black
Flexibility	Medium
Inside Diameter	16.9 mm
Material	Galvanized Steel Core with LFH Jacket and Stainless Steel Overbraid
Nominal Size	1/2 in
Number of Batteries	0
Outside Diameter	21.5 mm
Product Name	ADAPTAFLEX
Product Type	Medium Flexibility Conduit
Radius	80 mm
Special Functions	High UV Protection, Low Fire Hazard
UPC	786210248530

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	7TK001224
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	LFH-SPSS20/25M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

