

PRODUCT-DETAILS

PKCSSS28/BL/50M

S/S BRD PKCS28 50M REELS



General Information

Extended Product Type	PKCSSS28/BL/50M
Product ID	7TCA296100R0088
EAN	5020963015984
Catalog Description	S/S BRD PKCS28 50M REELS
Long Description	Standard Weight, High Flexibility Conduit, Nominal Conduit Size 28mm, NW Conduit Size 23, Coarse Conduit Pitch, Outside Diameter 28.4mm, Inside Diameter 21.7mm, Static Bend Radius 65mm, Reel Length 50 Meters, Polyketone with Stainless Steel Overbraid, Black

Ordering

EAN	5020963015984
-----	---------------

Dimensions

Product Net Depth / Length	50 m
Product Net Weight	6.61 lb 2.998 kg

Container Information

Package Level 1 Units	1 piece
Package Level 2 Units	1 piece

Package Level 2 Width	1 in 25 mm
Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Nuclear - Extreme Temperature or Underground Environments
Brand / Label	Adaptaflex
Color	Black
Flexibility	High
Inside Diameter	21.7 mm
Material	Polyketone with Stainless Steel Overbraid
Nominal Size	28 mm
Number of Batteries	0
Outside Diameter	28.4 mm
Product Name	SS FLEX CONDUIT
Product Type	Standard Weight Conduit with Coarse Pitch and Stainless Steel Overbraid
Radius	65 mm
Special Functions	Very High UV Protection and Fatigue Life
UPC	786210270395

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	PKCSSS28/BL/50M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	PKCSSS28/BL/50M

Classifications

ETIM 6	EC001175 - Corrugated plastic hose
ETIM 7	EC001175 - Corrugated plastic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

