

PRODUCT-DETAILS

PKCSSS34/BL/25M

S/S BRD PKCS34



General Information

Extended Product Type	PKCSSS34/BL/25M
Product ID	7TCA296100R0089
EAN	5020963048135
Catalog Description	S/S BRD PKCS34
Long Description	Standard Weight, High Flexibility Conduit, Nominal Conduit Size 34mm, NW Conduit Size 29, Coarse Conduit Pitch, Outside Diameter 34.3mm, Inside Diameter 27.7mm, Static Bend Radius 80mm, Reel Length 25 Meters, Polyketone with Stainless Steel Overbraid, Black

Ordering

EAN	5020963048135
-----	---------------

Dimensions

Product Net Depth / Length	25 m
Product Net Weight	6.61 lb 2.998 kg

Container Information

Package Level 1 Units	1 piece
Package Level 2 Units	1 piece

Package Level 2 Width	1 in 25 mm
Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Nuclear - Extreme Temperature or Underground Environments
Brand / Label	Adaptaflex
Color	Black
Flexibility	High
Inside Diameter	27.7 mm
Material	Polyketone with Stainless Steel Overbraid
Nominal Size	34 mm
Number of Batteries	0
Outside Diameter	34.3 mm
Product Name	ADAPTAFLEX
Product Type	Standard Weight Conduit with Coarse Pitch and Stainless Steel Overbraid
Radius	85 mm
Special Functions	Very High UV Protection and Fatigue Life
UPC	786210270401

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	PKCSSS34/BL/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	PKCSSS34/BL/25M

Classifications

ETIM 6	EC001175 - Corrugated plastic hose
ETIM 7	EC001175 - Corrugated plastic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

