

PRODUCT-DETAILS

PKCSTC34/BL/25M

T/C BRD PKCS34



General Information

Extended Product Type	PKCSTC34/BL/25M
Product ID	7TCA296100R0092
EAN	5020963050626
Catalog Description	T/C BRD PKCS34
Long Description	Highly Flexible Conduit, Nominal Conduit Size 34mm, NW Conduit Size 29, Course Conduit Pitch, Outside Diameter 36.0mm, Inside Diameter 27.7mm, Static Bend Radius 80mm, Reel Length 25 Meters, Polyketone with Tinner Copper Overbraid

Ordering

EAN	5020963050626
-----	---------------

Dimensions

Product Net Depth / Length	25 m
Product Net Weight	27 lb 12.245 kg

Container Information

Package Level 1 Units	1 piece
Package Level 2 Units	1 piece

Package Level 2 Width	1 in 25 mm
Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Nuclear, Extreme Temperature, Underground Environments
Brand / Label	Adaptaflex
Flexibility	High
Inside Diameter	27.7 mm
Material	Polyketone
Nominal Size	34 mm
Number of Batteries	0
Outside Diameter	36.0 mm
Product Name	ADAPTAFLEX
Product Type	Standard Weight Conduit with Coarse Pitch and Tinned Copper Overbraid
Radius	80 mm
Special Functions	Very High UV Protection and Fatigue Life
UPC	786210270425

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	PKCSTC34/BL/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	PKCSTC34/BL/25M

Classifications

ETIM 6	EC001175 - Corrugated plastic hose
ETIM 7	EC001175 - Corrugated plastic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

