
PRODUCT-DETAILS

PKFSSS13/BL/25M

S/S BRD PK COND NC13 25M BLK



General Information

Extended Product Type	PKFSSS13/BL/25M
Product ID	7TCA296100R0102
EAN	5020963048326
Catalog Description	S/S BRD PK COND NC13 25M BLK
Long Description	Standard Weight, High Flexibility Conduit, Nominal Conduit Size 13mm, NW Conduit Size 10, Fine Conduit Pitch, Outside Diameter 13.2mm, Inside Diameter 10.0mm, Static Bend Radius 35mm, Reel Length 25 Meters, Polyketone with Stainless Steel Overbraid, Black

Ordering

EAN	5020963048326
-----	---------------

Dimensions

Product Net Depth / Length	25 m
Product Net Weight	1.38 lb 625.85 g

Container Information

Package Level 1 Units	1 piece
Package Level 2 Units	1 piece

Package Level 2 Width	1 in 25 mm
Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Nuclear - Extreme Temperature or Underground Environments
Brand / Label	Adaptaflex
Color	Black
Flexibility	High
Inside Diameter	10.0 mm
Material	Polyketone with Stainless Steel Overbraid
Nominal Size	13 mm
Number of Batteries	0
Outside Diameter	13.2 mm
Product Name	PLASTIC CONDUIT
Product Type	Standard Weight Conduit with Fine Pitch and Stainless Steel Overbraid
Radius	35 mm
Special Functions	Very High UV Protection and Fatigue Life
UPC	786210270500

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	PKFSSS13/BL/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	PKFSSS13/BL/25M

Classifications

ETIM 6	EC001175 - Corrugated plastic hose
ETIM 7	EC001175 - Corrugated plastic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

