

PRODUCT-DETAILS

PKFSTC13/BL/25M

TIN/COPPER BRAIDED PKFS13



General Information

Extended Product Type	PKFSTC13/BL/25M
Product ID	7TCA296100R0110
EAN	5020963788079
Catalog Description	TIN/COPPER BRAIDED PKFS13
Long Description	Highly Flexible Conduit, Nominal Conduit Size 13mm, NW Conduit Size 10, Fine Conduit Pitch, Outside Diameter 14.1mm, Inside Diameter 10.0mm, Static Bend Radius 35mm, Reel Length 25 Meters, Polyketone with Tinner Copper Overbraid

Ordering

EAN	5020963788079
-----	---------------

Dimensions

Product Net Depth / Length	25 m
Product Net Weight	1.38 lb 625.85 g

Container Information

Package Level 1 Units	1 piece
Package Level 2 Units	1 piece

Package Level 2 Width	1 in 25 mm
Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Nuclear, Extreme Temperature, Underground Environments
Brand / Label	Adaptaflex
Flexibility	High
Inside Diameter	10.0 mm
Material	Polyketone
Nominal Size	13 mm
Number of Batteries	0
Outside Diameter	14.1 mm
Product Name	ADAPTAFLEX
Product Type	Standard Weight Conduit with Fine Pitch and Tinned Copper Overbraid
Radius	35 mm
Special Functions	Very High UV Protection and Fatigue Life
UPC	786210243498

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	PKFSTC13/BL/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	PKFSTC13/BL/25M

Classifications

ETIM 6	EC001175 - Corrugated plastic hose
ETIM 7	EC001175 - Corrugated plastic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

