

PRODUCT-DETAILS

PRCSS54/25M

PRCS54 SS/STL BRD CONDUIT25M



General Information

Extended Product Type	PRCSS54/25M
Product ID	7TCA296100R0127
EAN	5020963028304
Catalog Description	PRCS54 SS/STL BRD CONDUIT25M
Long Description	Standard Weight Conduit, Nominal Conduit Size 54mm, NW Conduit Size 48, Coarse Conduit Pitch, Outside Diameter 42.5mm, Inside Diameter 35.1mm, Static Bend Radius 90mm, Reel Length 25 Meters, Modified Polyamide (Nylon) 6 with Stainless Steel Overbraid, Black

Ordering

EAN	5020963028304
-----	---------------

Dimensions

Product Net Depth / Length	25 m
Product Net Weight	52.64 lb 23.873 kg

Container Information

Package Level 1 Units	1 piece
Package Level 2 Units	1 piece

Package Level 2 Width	1 in 25 mm
Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Indoors, Public Areas, Rail Infrastructure
Brand / Label	Adaptaflex
Color	Black
Flexibility	High
Inside Diameter	35.1 mm
Material	Modified Polyamide/Nylon 6 with Stainless Steel Overbraided
Nominal Size	42 mm
Number of Batteries	0
Outside Diameter	42.5 mm
Product Name	"flexible conduit, nylon"
Product Type	Standard Weight Conduit with Coarse Pitch and Stainless Steel Overbraided
Radius	90 mm
Special Functions	Very High UV Protection
UPC	786210243665

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	PRC5554/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	PRC5554/25M

Classifications

ETIM 6	EC001175 - Corrugated plastic hose
ETIM 7	EC001175 - Corrugated plastic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

