

PRODUCT-DETAILS

SPLB40/M40/A

M40 A TYPE FITTING



General Information

Extended Product Type	SPLB40/M40/A
Product ID	7TCA296100R0164
EAN	5020963025105
Catalog Description	M40 A TYPE FITTING
Long Description	Nickel Plated Brass Straight Fitting with Fixed External Thread, Nominal Conduit Size 40 Millimeters, IP68 Rating, Metric Thread Size M40

Ordering

EAN	5020963025105
-----	---------------

Dimensions

Product Net Weight	1.22 lb 553.288 g
--------------------	----------------------

Container Information

Package Level 2 Units	2 piece
Package Level 2 Width	1 in 25 mm
Package Level 2 Height	1 in 25 mm

Package Level 2 Depth /
Length

1 in
25 mm

Additional Information

Application	For Insertion into Threaded Entries or Knockout to Connect Conduit
Brand / Label	Adaptaflex
Cable Entry Position	M40 Thread
Color	Metallic
Material	Brass
Number of Batteries	0
Product Name	ADAPTAFLEX
Product Type	Conduit Fitting with Metric Threads
Size	1-1/4 Inch
Surface Finishing	Nickel Plated
UPC	786210274744

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPLB40/M40/A
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPLB40/M40/A

Classifications

ETIM 6	EC001180 - Screw connection for protective metallic hose
ETIM 7	EC001180 - Screw connection for protective metallic hose
UNSPSC	39121311
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4441 >> Electrical fittings

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

