

PRODUCT-DETAILS

# SPLHCB20/25M

## STL BRAIDED SPLHC20 FLEX 25M



### General Information

Extended Product Type	SPLHCB20/25M
Product ID	7TCA296100R0170
EAN	5020963011955
Catalog Description	STL BRAIDED SPLHC20 FLEX 25M
Long Description	Liquid Tight, Extreme Temperature Covered Steel Flexible Conduit with Stainless Steel Overbraid, Medium Flexibility, Nominal Conduit Size 20mm, Outside Diameter 21.1mm, Inside Diameter 15.9mm, Static Bend Radius 80mm, Reel Length 25 Meters, Thermoplastic Rubber Cover with Galvanised Steel Core, Black

### Ordering

EAN	5020963011955
-----	---------------

### Dimensions

Product Net Depth / Length	25 m
Product Net Weight	32.45 lb 14.717 kg

### Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in

	25 mm
Package Level 2 Height	1 in
	25 mm
Package Level 2 Depth / Length	1 in
	25 mm

### Additional Information

Application	Liquid Tight - Extreme Temperature Environments
Brand / Label	Adaptaflex
Color	Black
Flexibility	Medium
Inside Diameter	15.9 mm
Material	Galvanized Steel Core with Thermoplastic Rubber Cover
Nominal Size	1/2 in NC20
Number of Batteries	0
Outside Diameter	21.1 mm
Product Name	FLEXIBLE METAL CONDUIT
Product Type	Extreme Temperature Flexible Conduit
Radius	80 mm
UPC	786210245508

### Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPLHCB20/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPLHCB20/25M

### Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

### Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

