

PRODUCT-DETAILS

# SPLHCB40/25M

## LQT BRD SPLHC40 25M REELS



### General Information

Extended Product Type	SPLHCB40/25M
Product ID	7TCA296100R0175
EAN	5020963010705
Catalog Description	LQT BRD SPLHC40 25M REELS
Long Description	Liquid Tight, Extreme Temperature Covered Steel Flexible Conduit with Stainless Steel Braid, Medium Flexibility, Nominal Conduit Size 40mm, Outside Diameter 41.8mm, Inside Diameter 35.4mm, Static Bend Radius 180mm, Reel Length 25 Meters, Thermoplastic Rubber Cover with Galvanised Steel Core, Black

### Ordering

EAN	5020963010705
-----	---------------

### Dimensions

Product Net Depth / Length	25 m
Product Net Weight	62.01 lb 28.122 kg

### Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in

	25 mm
Package Level 2 Height	1 in
	25 mm
Package Level 2 Depth / Length	1 in
	25 mm

### Additional Information

Application	Liquid Tight - Extreme Temperature Environments
Brand / Label	Adaptaflex
Color	Black
Flexibility	Medium
Inside Diameter	35.4 mm
Material	Galvanized Steel Core with Thermoplastic Rubber Cover
Nominal Size	1-1/4 in NC40
Number of Batteries	0
Outside Diameter	41.8 mm
Product Name	ADAPTAFLEX
Product Type	Extreme Temperature Flexible Conduit
Radius	180 mm
UPC	786210274751

### Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPLHCB40/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPLHCB40/25M

### Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

### Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

