

PRODUCT-DETAILS

SPTC10/25M

STEEL PVC BRAID COND 25M REELS



General Information

Extended Product Type	SPTC10/25M
Product ID	7TCA296100R0180
EAN	5020963789588
Catalog Description	STEEL PVC BRAID COND 25M REELS
Long Description	Highly Flexible Conduit, Nominal Conduit Size 10mm, Outside Diameter 10.0mm, Inside Diameter 6.8mm, Static Bend Radius 25mm, Reel Length 25 Meters, Galvanised Steel Core with PVC Jacket and Tinned Copper Overbraid, Black

Ordering

EAN	5020963789588
-----	---------------

Dimensions

Product Net Depth / Length	25 m
Product Net Weight	6.67 lb 3.025 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	6 in 152 mm

Package Level 2 Height	9 in 229 mm
Package Level 2 Depth / Length	9 in 229 mm

Additional Information

Application	Indoors / Outdoors - Enhanced EMI Screen - High Abrasion Resistance
Brand / Label	Adaptaflex
Color	Black
Flexibility	High
Inside Diameter	6.8 mm
Material	Galvanized Steel Core, Tinned Copper Overbraid with PVC Jacket
Nominal Size	1/4 in 10 mm
Number of Batteries	0
Outside Diameter	10.0 mm
Product Name	flexible metal conduit
Product Type	High Flexibility Conduit
Radius	25 mm
Special Functions	Very High UV Protection
UPC	786210247403

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPTC10/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPTC10/25M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

