

PRODUCT-DETAILS

# SPTC32/10M

## SP32 T/C BRAID FLEX 10M



### General Information

Extended Product Type	SPTC32/10M
Product ID	7TCA296100R0186
EAN	5020963786983
Catalog Description	SP32 T/C BRAID FLEX 10M
Long Description	Highly Flexible Conduit, Nominal Conduit Size 32mm, Outside Diameter 34.0mm, Inside Diameter 28.1mm, Static Bend Radius 60mm, Reel Length 10 Meters, Galvanised Steel Core with PVC Jacket and Tinned Copper Overbraid, Black

### Ordering

EAN	5020963786983
-----	---------------

### Dimensions

Product Net Depth / Length	10 m
Product Net Weight	24.25 lb 10.998 kg

### Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

---

### Additional Information

Application	Indoors / Outdoors - Enhanced EMI Screen - High Abrasion Resistance
Brand / Label	Adaptaflex
Color	Black
Flexibility	High
Inside Diameter	28.1 mm
Material	Galvanized Steel Core, Tinned Copper Overbraid with PVC Jacket
Nominal Size	1 in
Number of Batteries	0
Outside Diameter	34.0 mm
Product Name	flexible metal conduit
Product Type	High Flexibility Conduit
Radius	60 mm
Special Functions	Very High UV Protection
UPC	786210247533

---

### Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPTC32/10M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPTC32/10M

---

### Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

---

### Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

