

PRODUCT-DETAILS

SPTC40/10M

SP T/C BR FLEX NC40 10M



General Information

Extended Product Type	SPTC40/10M
Product ID	7TCA296100R0187
EAN	5020963018336
Catalog Description	SP T/C BR FLEX NC40 10M
Long Description	Highly Flexible Conduit, Nominal Conduit Size 40mm, Outside Diameter 43.6mm, Inside Diameter 37.7mm, Static Bend Radius 80mm, Reel Length 10 Meters, Galvanised Steel Core with PVC Jacket and Tinned Copper Overbraid, Black

Ordering

EAN	5020963018336
-----	---------------

Dimensions

Product Net Depth / Length	10 m
Product Net Weight	20.86 lb 9.46 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Indoors / Outdoors - Enhanced EMI Screen - High Abrasion Resistance
Brand / Label	Adaptaflex
Color	Black
Flexibility	High
Inside Diameter	37.7 mm
Material	Galvanized Steel Core, Tinned Copper Overbraid with PVC Jacket
Nominal Size	1-1/4 in
Number of Batteries	0
Outside Diameter	43.6 mm
Product Name	flexible metal conduit
Product Type	High Flexibility Conduit
Radius	80 mm
Special Functions	Very High UV Protection
UPC	786210247540

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPTC40/10M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPTC40/10M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

