

PRODUCT-DETAILS

SSB16/25M

S.STL BRD S.STL COND NC16 25M



General Information

Extended Product Type	SSB16/25M
Product ID	7TCA296100R0191
EAN	5020963052002
Catalog Description	S.STL BRD S.STL COND NC16 25M
Long Description	Low Fire Hazard, High Flexibility, Covered Steel Conduit, Nominal Conduit Size 16mm, Outside Diameter 17.5mm, Inside Diameter 13.0mm, Static Bend Radius 35mm, Reel Length 25 Meters, 316 Stainless Steel Core and Overbraid

Ordering

EAN	5020963052002
-----	---------------

Dimensions

Product Net Depth / Length	25 m
Product Net Weight	8.6 lb 3.9 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Indoors / Outdoors - Standard EMI Screen - Very High Abrasion Resistance
Brand / Label	Adaptaflex
Flexibility	High
Inside Diameter	13.0 mm
Material	Stainless Steel Core and Overbraid
Nominal Size	3/8 in 16 mm
Number of Batteries	0
Outside Diameter	17.5 mm
Product Name	ADAPTAFLEX
Product Type	Low Fire Hazard Conduit
Radius	35 mm
Special Functions	Very High UV Protection and High Fatigue Life
UPC	786210260709

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SSB16/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SSB16/25M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

