

PRODUCT-DETAILS

STC20/25M

STL T/C BRAIDED COND 25M REELS



General Information

Extended Product Type	STC20/25M
Product ID	7TCA296100R0205
EAN	5020963012495
Catalog Description	STL T/C BRAIDED COND 25M REELS
Long Description	Low Fire Hazard, High Flexibility Conduit, Nominal Conduit Size 20mm, Outside Diameter 21.5mm, Inside Diameter 16.9mm, Static Bend Radius 45mm, Reel Length 25 Meters, Galvanised Steel Core with Tinned Copper Overbraid

Ordering

EAN	5020963012495
-----	---------------

Dimensions

Product Net Depth / Length	25 m
Product Net Weight	13.01 lb 5.9 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Galvanised Steel Core with Tinned Copper Overbraid
Brand / Label	Adaptaflex
Flexibility	High
Inside Diameter	16.9 mm
Material	Galvanized Steel Core with Tinned Copper Overbraid
Nominal Size	1/2 in
Number of Batteries	0
Outside Diameter	21.5 mm
Product Name	ADAPTAFLEX
Product Type	Low Fire Hazard Conduit
Radius	45 mm
Special Functions	Very High UV Protection
UPC	786210260846

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	STC20/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	STC20/25M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

