

PRODUCT-DETAILS

STC25/25M

STL T/C BRAIDED NC25 25M REELS



General Information

Extended Product Type	STC25/25M
Product ID	7TCA296100R0206
EAN	5020963013959
Catalog Description	STL T/C BRAIDED NC25 25M REELS
Long Description	Low Fire Hazard, High Flexibility Conduit, Nominal Conduit Size 25mm, Outside Diameter 26.0mm, Inside Diameter 21.4mm, Static Bend Radius 55mm, Reel Length 25 Meters, Galvanised Steel Core with Tinned Copper Overbraid

Ordering

EAN	5020963013959
-----	---------------

Dimensions

Product Net Depth / Length	25 m
Product Net Weight	15.43 lb 6.998 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Galvanised Steel Core with Tinned Copper Overbraid
Brand / Label	Adaptaflex
Flexibility	High
Inside Diameter	21.4 mm
Material	Galvanized Steel Core with Tinned Copper Overbraid
Nominal Size	3/4 in
Number of Batteries	0
Outside Diameter	26.0 mm
Product Name	ADAPTAFLEX
Product Type	Low Fire Hazard Conduit
Radius	55 mm
Special Functions	Very High UV Protection
UPC	786210260853

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	STC25/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	STC25/25M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

