

PRODUCT-DETAILS

# STC32/25M

## S32 T/C BRAID FLEX 25M REELS



### General Information

Extended Product Type	STC32/25M
Product ID	7TCA296100R0208
EAN	5020963013980
Catalog Description	S32 T/C BRAID FLEX 25M REELS
Long Description	Low Fire Hazard, High Flexibility Conduit, Nominal Conduit Size 32mm, Outside Diameter 34.0mm, Inside Diameter 28.1mm, Static Bend Radius 60mm, Reel Length 25 Meters, Galvanised Steel Core with Tinned Copper Overbraid

### Ordering

EAN	5020963013980
-----	---------------

### Dimensions

Product Net Depth / Length	25 m
Product Net Weight	51.8 lb 23.492 kg

### Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

### Additional Information

Application	Galvanised Steel Core with Tinned Copper Overbraid
Brand / Label	Adaptaflex
Flexibility	High
Inside Diameter	28.1 mm
Material	Galvanized Steel Core with Tinned Copper Overbraid
Nominal Size	1 in
Number of Batteries	0
Outside Diameter	34.0 mm
Product Name	ADAPTAFLEX
Product Type	Low Fire Hazard Conduit
Radius	60 mm
Special Functions	Very High UV Protection
UPC	786210260860

### Certificates and Declarations (Document Number)

Data Sheet, Technical Information	STC32/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	STC32/25M

### Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

### Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

