

PRODUCT-DETAILS

STC40/10M

STL T/C BR FLEX 10M REEL



General Information

Extended Product Type	STC40/10M
Product ID	7TCA296100R0209
EAN	5020963047251
Catalog Description	STL T/C BR FLEX 10M REEL
Long Description	Low Fire Hazard, High Flexibility Conduit, Nominal Conduit Size 40mm, Outside Diameter 43.6mm, Inside Diameter 37.7mm, Static Bend Radius 80mm, Reel Length 10 Meters, Galvanised Steel Core with Tinned Copper Overbraid

Ordering

EAN	5020963047251
-----	---------------

Dimensions

Product Net Depth / Length	10 m
Product Net Weight	16.51 lb 7.488 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Galvanised Steel Core with Tinned Copper Overbraid
Brand / Label	Adaptaflex
Flexibility	High
Inside Diameter	37.7 mm
Material	Galvanized Steel Core with Tinned Copper Overbraid
Nominal Size	1-1/4 in
Number of Batteries	0
Outside Diameter	43.6 mm
Product Name	ADAPTAFLEX
Product Type	Low Fire Hazard Conduit
Radius	80 mm
Special Functions	Very High UV Protection
UPC	786210260877

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	STC40/10M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	STC40/10M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

