

PRODUCT-DETAILS

STC50/10M

STL T/C BR FLEX 10M NC50



General Information

Extended Product Type	STC50/10M
Product ID	7TCA296100R0211
EAN	5020963010514
Catalog Description	STL T/C BR FLEX 10M NC50
Long Description	Low Fire Hazard, High Flexibility Conduit, Nominal Conduit Size 50mm, Outside Diameter 56.0mm, Inside Diameter 48.4mm, Static Bend Radius 90mm, Reel Length 10 Meters, Galvanised Steel Core with Tinned Copper Overbraid

Ordering

EAN	5020963010514
-----	---------------

Dimensions

Product Net Depth / Length	10 m
Product Net Weight	20.7 lb 9.388 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Galvanised Steel Core with Tinned Copper Overbraid
Brand / Label	Adaptaflex
Flexibility	High
Inside Diameter	48.4 mm
Material	Galvanized Steel Core with Tinned Copper Overbraid
Nominal Size	1-1/2 in
Number of Batteries	0
Outside Diameter	56.0 mm
Product Name	ADAPTAFLEX
Product Type	Low Fire Hazard Conduit
Radius	90 mm
Special Functions	Very High UV Protection
UPC	786210260884

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	STC50/10M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	STC50/10M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

