

PRODUCT-DETAILS

SS12/25M

25M X SS12 CONDUIT



General Information

Extended Product Type	SS12/25M
Product ID	7TCA296120R0008
EAN	5020963005855
Catalog Description	25M X SS12 CONDUIT
Long Description	Inherent Low Fire Hazard Conduit, Nominal Conduit Size 12mm, Outside Diameter 13.0mm, Inside Diameter 10.3mm, Static Bend Radius 30mm, Reel Length 25 Meters, 316 Stainless Steel, Corrosion Resistant

Ordering

EAN	5020963005855
-----	---------------

Dimensions

Product Net Depth / Length	25 m
Product Net Weight	5.79 lb 2.626 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Indoors / Outdoors - Corrosive Environments
Brand / Label	Adaptaflex
Flexibility	Very High
Inside Diameter	10.3 mm
Material	Stainless Steel
Nominal Size	5/16 in
Number of Batteries	0
Outside Diameter	13.0 mm
Product Name	flexible metal conduit
Product Type	Low Fire Hazard Conduit
Radius	30 mm
Special Functions	Very High UV Protection and Fatigue Life
UPC	786210249537

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SS12/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SS12/25M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

