

PRODUCT-DETAILS

# SS16/25M

## NC16 SS CONDUIT NW-16 LEN 25 METER



### General Information

Extended Product Type	SS16/25M
Product ID	7TCA296120R0014
EAN	5020963007224
Catalog Description	NC16 SS CONDUIT NW-16 LEN 25 METER
Long Description	Inherent Low Fire Hazard Conduit, Nominal Conduit Size 16mm, Outside Diameter 16.0mm, Inside Diameter 13.0mm, Static Bend Radius 35mm, Reel Length 25 Meters, 316 Stainless Steel, Corrosion Resistant

### Ordering

EAN	5020963007224
-----	---------------

### Dimensions

Product Net Depth / Length	25 m
Product Net Weight	9.07 lb 4.113 kg

### Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

## Additional Information

Application	Indoors / Outdoors - Corrosive Environments
Brand / Label	Adaptaflex
Flexibility	Very High
Inside Diameter	13.0 mm
Material	Stainless Steel
Nominal Size	3/8 in 16 mm
Number of Batteries	0
Outside Diameter	16.0 mm
Product Name	flexible metal conduit
Product Type	Low Fire Hazard Conduit
Radius	35 mm
Special Functions	Very High UV Protection and Fatigue Life
UPC	786210249544

## Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SS16/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SS16/25M

## Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

## Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

