

PRODUCT-DETAILS

SS20/25M

25M X SS20 CONDUIT



General Information

Extended Product Type	SS20/25M
Product ID	7TCA296120R0020
EAN	5020963005909
Catalog Description	25M X SS20 CONDUIT
Long Description	Inherent Low Fire Hazard Conduit, Nominal Conduit Size 20mm, Outside Diameter 20.5mm, Inside Diameter 16.9mm, Static Bend Radius 45mm, Reel Length 25 Meters, 316 Stainless Steel, Corrosion Resistant

Ordering

EAN	5020963005909
-----	---------------

Dimensions

Product Net Depth / Length	25 m
Product Net Weight	10.51 lb 4.766 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Indoors / Outdoors - Corrosive Environments
Brand / Label	Adaptaflex
Flexibility	Very High
Inside Diameter	16.9 mm
Material	Stainless Steel
Nominal Size	1/2 in
Number of Batteries	0
Outside Diameter	20.5 mm
Product Name	flexible metal conduit
Product Type	Low Fire Hazard Conduit
Radius	45 mm
Special Functions	Very High UV Protection and Fatigue Life
UPC	786210249551

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SS20/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SS20/25M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

