

PRODUCT-DETAILS

SS25/500M

500M X SS25 CONDUIT



General Information

Extended Product Type	SS25/500M
Product ID	7TCA296120R0029
EAN	5020963030673
Catalog Description	500M X SS25 CONDUIT
Long Description	Inherent Low Fire Hazard Conduit, Nominal Conduit Size 25mm, Outside Diameter 25.0mm, Inside Diameter 21.4mm, Static Bend Radius 55mm, Reel Length 500 Meters, 316 Stainless Steel, Corrosion Resistant

Ordering

EAN	5020963030673
-----	---------------

Dimensions

Product Net Depth / Length	500 m
Product Net Weight	255.74 lb 115.982 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Indoors / Outdoors - Corrosive Environments
Brand / Label	Adaptaflex
Flexibility	Very High
Inside Diameter	21.4 mm
Material	Stainless Steel
Nominal Size	3/4 in
Number of Batteries	0
Outside Diameter	25.0 mm
Product Name	ADAPTAFLEX
Product Type	Low Fire Hazard Conduit
Radius	55 mm
Special Functions	Very High UV Protection and Fatigue Life
UPC	786210260808

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SS25/500M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SS25/500M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

