

PRODUCT-DETAILS

# LFH-SP12/50M

## 50M X LFH-SP12 CONDUIT



### General Information

Extended Product Type	LFH-SP12/50M
Product ID	7TCA296130R0003
EAN	5020963777981
Catalog Description	50M X LFH-SP12 CONDUIT
Long Description	Low Fire Hazard, Medium Flexibility Conduit, Nominal Conduit Size 12mm, Outside Diameter 14.0mm, Inside Diameter 10.3mm, Static Bend Radius 30mm, IP54 and IP65 Rating, Galvanised Steel Core with Low Fire Hazard Jacket, Reel Length 50 Meters, Black

### Ordering

EAN	5020963777981
-----	---------------

### Dimensions

Product Net Depth / Length	50 m
Product Net Weight	16.31 lb 7.397 kg

### Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in

	25 mm
Package Level 2 Height	1 in
	25 mm
Package Level 2 Depth / Length	1 in
	25 mm

### Additional Information

Application	Rail, Buildings - Where Low Smoke & Toxicity is a Primary Concern
Brand / Label	Adaptaflex
Color	Black
Flexibility	Medium
Inside Diameter	10.3 mm
Material	Galvanized Steel Core with Low Fire Hazard Jacket
Nominal Size	5/16 in
Number of Batteries	0
Outside Diameter	14.0 mm
Product Name	ADAPTAFLEX
Product Type	Medium Flexibility Conduit
Radius	30 mm
Special Functions	High UV Protection, Low Fire Hazard
UPC	786210248554

### Certificates and Declarations (Document Number)

Data Sheet, Technical Information	LFH-SP12/50M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	LFH-SP12/50M

### Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

### Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

