

PRODUCT-DETAILS

# LFH-SP16/25M

## 25M X LFH-SP16 CONDUIT



### General Information

Extended Product Type	LFH-SP16/25M
Product ID	7TCA296130R0004
EAN	5020963046384
Catalog Description	25M X LFH-SP16 CONDUIT
Long Description	Low Fire Hazard, Medium Flexibility Conduit, Nominal Conduit Size 16mm, Outside Diameter 17.0mm, Inside Diameter 13.0mm, Static Bend Radius 35mm, IP54 and IP65 Rating, Galvanised Steel Core with Low Fire Hazard Jacket, Reel Length 25 Meters, Black

### Ordering

EAN	5020963046384
-----	---------------

### Dimensions

Product Net Depth / Length	25 m
Product Net Weight	12.68 lb 5.751 kg

### Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in

	25 mm
Package Level 2 Height	1 in
	25 mm
Package Level 2 Depth / Length	1 in
	25 mm

### Additional Information

Application	Rail, Buildings - Where Low Smoke & Toxicity is a Primary Concern
Brand / Label	Adaptaflex
Color	Black
Flexibility	Medium
Inside Diameter	13.0 mm
Material	Galvanized Steel Core with Low Fire Hazard Jacket
Nominal Size	3/8 in
	16 mm
Number of Batteries	0
Outside Diameter	17.0 mm
Product Name	ADAPTAFLX
Product Type	Medium Flexibility Conduit
Radius	35 mm
Special Functions	High UV Protection, Low Fire Hazard
UPC	786210248561

### Certificates and Declarations (Document Number)

Data Sheet, Technical Information	LFH-SP16/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	LFH-SP16/25M

### Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

### Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

