

PRODUCT-DETAILS

# LFH-SP20/25M

## 25M X LFH-SP20 CONDUIT



### General Information

Extended Product Type	LFH-SP20/25M
Product ID	7TCA296130R0007
EAN	5020963019654
Catalog Description	25M X LFH-SP20 CONDUIT
Long Description	Low Fire Hazard, Medium Flexibility Conduit, Nominal Conduit Size 20mm, Outside Diameter 21.5mm, Inside Diameter 16.9mm, Static Bend Radius 45mm, IP54 and IP65 Rating, Galvanised Steel Core with Low Fire Hazard Jacket, Reel Length 25 Meters, Black

### Ordering

EAN	5020963019654
-----	---------------

### Dimensions

Product Net Depth / Length	25 m
Product Net Weight	17.2 lb 7.8 kg

### Container Information

Package Level 1 Units	1 piece
Package Level 2 Units	1 piece

Package Level 2 Width	37 in 940 mm
Package Level 2 Height	17 in 432 mm
Package Level 2 Depth / Length	17 in 432 mm

### Additional Information

Application	Rail, Buildings - Where Low Smoke & Toxicity is a Primary Concern
Brand / Label	Adaptaflex
Color	Black
Flexibility	Medium
Inside Diameter	16.9 mm
Material	Galvanized Steel Core with Low Fire Hazard Jacket
Nominal Size	1/2 in
Number of Batteries	0
Outside Diameter	21.5 mm
Product Name	flexible metal conduit
Product Type	Medium Flexibility Conduit
Radius	45 mm
Special Functions	High UV Protection, Low Fire Hazard
UPC	786210277776

### Certificates and Declarations (Document Number)

Data Sheet, Technical Information	LFH-SP20/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	LFH-SP20/25M

### Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

### Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

