

PRODUCT-DETAILS

LFH-SP25/10M

10M X LFH-SP25 CONDUIT



General Information

Extended Product Type	LFH-SP25/10M
Product ID	7TCA296130R0010
EAN	5020963009976
Catalog Description	10M X LFH-SP25 CONDUIT
Long Description	Low Fire Hazard, Medium Flexibility Conduit, Nominal Conduit Size 25mm, Outside Diameter 26.0mm, Inside Diameter 21.4mm, Static Bend Radius 55mm, IP54 and IP65 Rating, Galvanised Steel Core with Low Fire Hazard Jacket, Reel Length 10 Meters, Black

Ordering

EAN	5020963009976
-----	---------------

Dimensions

Product Net Depth / Length	10 m
Product Net Weight	8.16 lb 3.701 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in

	25 mm
Package Level 2 Height	1 in
	25 mm
Package Level 2 Depth / Length	1 in
	25 mm

Additional Information

Application	Rail, Buildings - Where Low Smoke & Toxicity is a Primary Concern
Brand / Label	Adaptaflex
Color	Black
Flexibility	Medium
Inside Diameter	21.4 mm
Material	Galvanized Steel Core with Low Fire Hazard Jacket
Nominal Size	3/4 in
Number of Batteries	0
Outside Diameter	26.0 mm
Product Name	flexible metal conduit
Product Type	Medium Flexibility Conduit
Radius	55 mm
Special Functions	High UV Protection, Low Fire Hazard
UPC	786210277790

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	LFH-SP25/10M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	LFH-SP25/10M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

