

PRODUCT-DETAILS

# LFH-SP25/50M

## LIMITED FIRE HAZARD STEEL COATED CO



### General Information

Extended Product Type	LFH-SP25/50M
Product ID	7TCA296130R0013
EAN	5020963046667
Catalog Description	LIMITED FIRE HAZARD STEEL COATED CO
Long Description	Low Fire Hazard, Medium Flexibility Conduit, Nominal Conduit Size 25mm, Outside Diameter 26.0mm, Inside Diameter 21.4mm, Static Bend Radius 55mm, IP54 and IP65 Rating, Galvanised Steel Core with Low Fire Hazard Jacket, Reel Length 50 Meters, Black

### Ordering

EAN	5020963046667
-----	---------------

### Dimensions

Product Net Depth / Length	50 m
Product Net Weight	40.81 lb 18.508 kg

### Container Information

Package Level 2 Units	7 piece
Package Level 2 Width	37 in

	940 mm
Package Level 2 Height	17 in
	432 mm
Package Level 2 Depth / Length	17 in
	432 mm

### Additional Information

Application	Rail, Buildings - Where Low Smoke & Toxicity is a Primary Concern
Brand / Label	Adaptaflex
Color	Black
Flexibility	Medium
Inside Diameter	21.4 mm
Material	Galvanized Steel Core with Low Fire Hazard Jacket
Nominal Size	3/4 in
Number of Batteries	0
Outside Diameter	26.0 mm
Product Name	ADAPTAFLEX
Product Type	Medium Flexibility Conduit
Radius	55 mm
Special Functions	High UV Protection, Low Fire Hazard
UPC	786210248578

### Certificates and Declarations (Document Number)

Data Sheet, Technical Information	LFH-SP25/50M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	LFH-SP25/50M

### Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

### Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

