

PRODUCT-DETAILS

LFH-SP40/10M

10M X LFH-SP40 CONDUIT



General Information

Extended Product Type	LFH-SP40/10M
Product ID	7TCA296130R0017
EAN	5020963050831
Catalog Description	10M X LFH-SP40 CONDUIT
Long Description	Low Fire Hazard, Medium Flexibility Conduit, Nominal Conduit Size 40mm, Outside Diameter 44.5mm, Inside Diameter 37.7mm, Static Bend Radius 80mm, IP54 and IP65 Rating, Galvanised Steel Core with Low Fire Hazard Jacket, Reel Length 10 Meters, Black

Ordering

EAN	5020963050831
-----	---------------

Dimensions

Product Net Depth / Length	10 m
Product Net Weight	20.92 lb 9.488 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in

	25 mm
Package Level 2 Height	1 in
	25 mm
Package Level 2 Depth / Length	1 in
	25 mm

Additional Information

Application	Rail, Buildings - Where Low Smoke & Toxicity is a Primary Concern
Brand / Label	Adaptaflex
Color	Black
Flexibility	Medium
Inside Diameter	37.7 mm
Material	Galvanized Steel Core with Low Fire Hazard Jacket
Nominal Size	1-1/4 in
Number of Batteries	0
Outside Diameter	44.5 mm
Product Name	flexible steel tubing
Product Type	Medium Flexibility Conduit
Radius	80 mm
Special Functions	High UV Protection, Low Fire Hazard
UPC	786210277820

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	LFH-SP40/10M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	LFH-SP40/10M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

