

PRODUCT-DETAILS

LFH-SP50/25M

25M X LFH-SP50 CONDUIT



General Information

Extended Product Type	LFH-SP50/25M
Product ID	7TCA296130R0020
EAN	5020963007736
Catalog Description	25M X LFH-SP50 CONDUIT
Long Description	Low Fire Hazard, Medium Flexibility Conduit, Nominal Conduit Size 50mm, Outside Diameter 55.0mm, Inside Diameter 48.4mm, Static Bend Radius 90mm, IP54 and IP65 Rating, Galvanised Steel Core with Low Fire Hazard Jacket, Reel Length 25 Meters, Black

Ordering

EAN	5020963007736
-----	---------------

Dimensions

Product Net Depth / Length	25 m
Product Net Weight	63.71 lb 28.893 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in

	25 mm
Package Level 2 Height	1 in
	25 mm
Package Level 2 Depth / Length	1 in
	25 mm

Additional Information

Application	Rail, Buildings - Where Low Smoke & Toxicity is a Primary Concern
Brand / Label	Adaptaflex
Color	Black
Flexibility	Medium
Inside Diameter	48.4 mm
Material	Galvanized Steel Core with Low Fire Hazard Jacket
Nominal Size	1-1/2 in
Number of Batteries	0
Outside Diameter	55.0 mm
Product Name	ADAPTAFLEX
Product Type	Medium Flexibility Conduit
Radius	90 mm
Special Functions	High UV Protection, Low Fire Hazard
UPC	786210248592

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	LFH-SP50/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	LFH-SP50/25M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

