

PRODUCT-DETAILS

# LFH-SP63/25M

## LFH-SP63 CONDUIT 25M REEL



### General Information

Extended Product Type	LFH-SP63/25M
Product ID	7TCA296130R0022
EAN	5020963019401
Catalog Description	LFH-SP63 CONDUIT 25M REEL
Long Description	Low Fire Hazard, Medium Flexibility Conduit, Nominal Conduit Size 63mm, Outside Diameter 64.5mm, Inside Diameter 57.5mm, Static Bend Radius 115mm, IP54 and IP65 Rating, Galvanised Steel Core with Low Fire Hazard Jacket, Reel Length 25 Meters, Black

### Ordering

EAN	5020963019401
-----	---------------

### Dimensions

Product Net Depth / Length	25 m
Product Net Weight	42.33 lb 19.197 kg

### Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in

	25 mm
Package Level 2 Height	1 in
	25 mm
Package Level 2 Depth / Length	1 in
	25 mm

### Additional Information

Application	Rail, Buildings - Where Low Smoke & Toxicity is a Primary Concern
Brand / Label	Adaptaflex
Color	Black
Flexibility	Medium
Inside Diameter	57.5 mm
Material	Galvanized Steel Core with Low Fire Hazard Jacket
Nominal Size	2 in
Number of Batteries	0
Outside Diameter	64.5 mm
Product Name	ADAPTAFLEX
Product Type	Medium Flexibility Conduit
Radius	115 mm
Special Functions	High UV Protection, Low Fire Hazard
UPC	786210248608

### Certificates and Declarations (Document Number)

Data Sheet, Technical Information	LFH-SP63/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	LFH-SP63/25M

### Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

### Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

