

PRODUCT-DETAILS

LFH-SP731/125/30M

1.25 SP731 LOW FIRE HAZARD



General Information

Extended Product Type	LFH-SP731/125/30M
Product ID	7TCA296130R0027
EAN	5020963009167
Catalog Description	1.25 SP731 LOW FIRE HAZARD
Long Description	Liquid Resistant, Low Fire Hazard Conduit, Size 1-1/4 Inch, IP54 and IP65 Rating, Polyolefin Covered Galvanised Steel, Length 30 Meters, Black

Ordering

EAN	5020963009167
-----	---------------

Dimensions

Product Net Depth / Length	30 m
Product Net Weight	51.3 lb 23.265 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Rail, Buildings - Where Low Smoke & Toxicity is a Primary Concern
Brand / Label	Adaptaflex
Color	Black
Flexibility	Medium
Material	Galvanized Steel Core with Low Fire Hazard Jacket
Nominal Size	1-1/4 in
Number of Batteries	0
Product Name	ADAPTAFLEX
Product Type	Medium Flexibility Conduit
Special Functions	High UV Protection, Low Fire Hazard
UPC	786210248639

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	LFH-SP731/125/30M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	LFH-SP731/125/30M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

