

PRODUCT-DETAILS

# SN20/BL/50M

## 50M X SN20/BLACK CONDUIT



### General Information

Extended Product Type	SN20/BL/50M
Product ID	7TCA296130R0040
EAN	5020963004117
Catalog Description	50M X SN20/BLACK CONDUIT
Long Description	Liquid Resistant Abrasion and Solvent Resistant Covered, Medium Flexibility Conduit, Nominal Conduit Size 20mm, Outside Diameter 21.5mm, Inside Diameter 16.9mm, Static Bend Radius 45mm, Reel Length 50 Meters, PA (Nylon) Jacket with Galvanised Steel Core, Black

### Ordering

EAN	5020963004117
-----	---------------

### Dimensions

Product Net Depth / Length	50 m
Product Net Weight	30.42 lb 13.796 kg

### Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	17 in

	432 mm
Package Level 2 Height	16 in
	406 mm
Package Level 2 Depth / Length	16 in
	406 mm

### Additional Information

Application	Indoors / Outdoors - Liquid, Abrasion and Solvent Resistant
Brand / Label	Adaptaflex
Color	Black
Flexibility	Medium
Inside Diameter	16.9 mm
Material	Galvanized Steel Core with Polyamide/Nylon 6 Jacket
Nominal Size	20 mm
Number of Batteries	0
Outside Diameter	21.5 mm
Product Name	flexible metal conduit
Product Type	Medium Flexibility Conduit
Radius	45 mm
Special Functions	Very High UV Protection
UPC	786210245157

### Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SN20/BL/50M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SN20/BL/50M

### Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

### Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

