

PRODUCT-DETAILS

LFH-SPSS40/10M

LFH-SP40 WITH SS OVERBRAID



General Information

Extended Product Type	LFH-SPSS40/10M
Product ID	7TCA296130R0051
EAN	5020963808760
Catalog Description	LFH-SP40 WITH SS OVERBRAID
Long Description	Low Fire Hazard, Medium Flexibility Conduit with Stainless Steel Overbraid, Nominal Conduit Size 40mm, Static Bend Radius 240mm, Galvanised Steel Core with Low Fire Hazard Jacket, Reel Length 10 Meters, Black

Ordering

EAN	5020963808760
-----	---------------

Dimensions

Product Net Depth / Length	10 m
Product Net Weight	21 lb 9.524 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Rail, Buildings - Where Low Smoke & Toxicity is a Primary Concern
Brand / Label	Adaptaflex
Color	Black
Flexibility	Medium
Material	Galvanized Steel Core with LFH Jacket and Stainless Steel Overbraid
Number of Batteries	0
Product Name	FLEXIBLE METALL CONDUIT
Product Type	Medium Flexibility Conduit
Special Functions	High UV Protection, Low Fire Hazard
UPC	786210211459

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	7TK001224
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	LFH-SPSS40/10M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

