


PRODUCT-DETAILS

# KFM20/50M

## 20MM BLACK PVC MEDIUM WEIGHT CORRUG



### General Information

Extended Product Type	KFM20/50M
Product ID	7TCA296140R0030
EAN	5020963009792
Catalog Description	20MM BLACK PVC MEDIUM WEIGHT CORRUG
Long Description	Medium Weight Conduit, Nominal Conduit Size 20mm, NW Conduit Size 17, Fine Conduit Pitch, Outside Diameter 19.8mm, Inside Diameter 14.3mm, Static Bend Radius 30mm, Reel Length 50 Meters, PVCu, Black

### Ordering

EAN	5020963009792
-----	---------------

### Dimensions

Product Net Depth / Length	50 m
Product Net Weight	7.61 lb 3.451 kg

### Container Information

Package Level 1 Units	6 piece
Package Level 1 Width	37 in 940 mm

Package Level 1 Height	17 in 432 mm
Package Level 1 Depth / Length	178 in 4521 mm
Package Level 2 Units	6 piece
Package Level 2 Width	38 in 965 mm
Package Level 2 Height	17 in 432 mm
Package Level 2 Depth / Length	17 in 432 mm
Package Level 3 Units	6 piece
Package Level 3 Width	37 in 940 mm
Package Level 3 Height	17 in 432 mm
Package Level 3 Depth / Length	17 in 432 mm

### Additional Information

Application	Indoors / Outdoors, General Purpose Applications
Brand / Label	Adaptaflex
Color	Black
Flexibility	Pliable
Inside Diameter	14.3 mm
Material	PVCu
Nominal Size	NW17
Number of Batteries	0
Outside Diameter	19.8 mm
Product Name	ADAPTAFLEX
Product Type	Medium Weight Conduit with Fine Pitch
Radius	30 mm
UPC	786210247984

### Certificates and Declarations (Document Number)

Data Sheet, Technical Information	KFM20/50M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	KFM20/50M

### Classifications

ETIM 6	EC001175 - Corrugated plastic hose
ETIM 7	EC001175 - Corrugated plastic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

---

## Categories

---

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

