

PRODUCT-DETAILS

# STC63/10M

## STL T/C BR FLEX 10M NC63



Product image  
not available

### General Information

Extended Product Type	STC63/10M
Product ID	7TCA296160R0104
EAN	5020963799525
Catalog Description	STL T/C BR FLEX 10M NC63
Long Description	Low Fire Hazard, High Flexibility Conduit, Nominal Conduit Size 63mm, Outside Reel Length 10 Meters, Galvanised Steel Core with Tinned Copper Overbraid

### Ordering

EAN	5020963799525
-----	---------------

### Dimensions

Product Net Depth / Length	10 m
Product Net Weight	15 lb 6.803 kg

### Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

### Additional Information

Application	Galvanised Steel Core with Tinned Copper Overbraid
Brand / Label	Adaptaflex
Flexibility	High
Material	Galvanized Steel Core with Tinned Copper Overbraid
Nominal Size	2 in
Number of Batteries	0
Product Name	STEEL CORE T/C OVERBRAID
Product Type	Low Fire Hazard Conduit
Special Functions	Very High UV Protection
UPC	786210313726

### Certificates and Declarations (Document Number)

Data Sheet, Technical Information	STC63/10M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	STC63/10M

### Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

### Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems



Product image  
not available