

PRODUCT-DETAILS

# SPL12/25M

## 12MM LIQUID TIGHT CONDUIT BLACK



### General Information

Extended Product Type	SPL12/25M
Product ID	7TCD012980R0287
EAN	5415022064643
Catalog Description	12MM LIQUID TIGHT CONDUIT BLACK
Long Description	Liquid Tight, Oil Resistant, Medium Flexibility Conduit, Nominal Conduit Size 12mm, Outside Diameter 14.2mm, Inside Diameter 10.0mm, Static Bend Radius 45mm, Reel Length 25 Meters, PVC Covering with Galvanised Steel Core, Black

### Ordering

EAN	5415022064643
-----	---------------

### Dimensions

Product Net Depth / Length	25 m
Product Net Weight	12.13 lb 5.501 kg

### Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

## Additional Information

Application	Liquid Tight - Indoors / Outdoors, Marine, Buildings
Brand / Label	Adaptaflex
Color	Black
Flexibility	Medium
Inside Diameter	10.0 mm
Material	Galvanized Steel Core with PVC Covering
Nominal Size	5/16 in NC12
Number of Batteries	0
Outside Diameter	14.2 mm
Product Name	NON-METALLIC CONDUIT
Product Type	Oil Resistant Conduit
Radius	45 mm
UPC	786209985156

## Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPL12/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPL12/25M

## Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

## Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

