





## X-TRACK | Spot sur rail triphasé

IP20 | IK02 | blanc - ral 9003



|   |  |
|---|--|
| Garantie<br><b>5ans</b>   | <b>L80B10</b><br>>50000h   |
| LED<br>COB<br>Bridgelux   | SDCM<br><b>&lt; 3</b>  |
| IRC<br>≥ <b>90Ra</b>  | <b>IP20</b>  |
| <br>FLICKER<br>FREE | <br>DRIVER<br><b>Philips</b><br>Xitanium |
| AC<br><b>220/240V</b>   |   |

| Référence | Puissance | Flux Lumineux | Température de couleur  | Faisceau          | PF         | Dimensions                | Options  |
|-----------|-----------|---------------|---|-------------------|------------|---------------------------|--|
| 851150    | 20 W ◀    | 1800 lm       |  2700K<br>-<br>3000K<br>-<br>4000K ◀<br>-<br>5000K | 12°<br>-<br>24° ◀ | > 0.9      | ø83 x (l)91 x (H)175 mm   | Finition : Gris - ral 9006<br>-<br>Gradation: DALI   TRIAC |
| 851152    | 32 W      | 3000 lm       |   | 30°<br>-<br>45° ◀ | > 0.9      | ø93 x (l)112 x (H)184 mm  |  |
| 851154    | 42 W ◀    | 4000 lm       |   | 60°               | > 0.9      | ø125 x (l)106 x (H)192 mm |  |
|           |           |               |   | à préciser        | à préciser |                           |  |

