

# TRMS 600A<sub>AC/DC</sub> MINI CURRENT CLAMP METER

## DCM450MINI



### Key Features :

- TRMS
- Display with 6000 counts and backlight
- Current up to 600A ac/dc
- Measurements also in Voltage Ac/DC , Resistance, Frequency, Capacitance and Temperature
- Non Contact Voltage detection
- Auto ranging
- Auto Power Off
- Safety rating: CATIII 600V



# DCM450MINI

## TRMS 600AAC/DC MINI CURRENT CLAMP METER

General	
Display	6000 counts
Sampling rate	3 times/sec
Auto power off	✓
Backlight	✓
Hold	✓
Auto-ranging	✓
DCA Zeroing	✓
Torch Light	✓
Low Battery Indication	✓
Jaw opening size	Φ26mm/1.0"
Drop test	4 feet drop test
Dimensions	210 x 69x 41 mm (8.2x 2.7 x 1.6 in)
Weight	about 247g(8.7oz)
Power Supply	3x1.5V AAA Batteries
Standars	EC 61010-1, IEC/EN61010-2-032
Safety rating	CAT III 600V/CAT IV 300V
Accesories included	Batteries, Manual, Carrying pouch

# DCM450MINI

## TRMS 600AAC/DC MINI CURRENT CLAMP METER

Specs		
FUNCTION	RANGE	RESOLUTION
TRMS		✓
AC Current	60.00A/600.0A AC	0.01A/0.1A
AC Voltage	600.0mV/6.000V/60.00V//600.0V	0.1mV/0.001V/0.01V//0.1V
DC Current	60.00A/600.0A AC	0.01A/0.1A
DC Voltage	600.0mV/6.000V/60.00V//600.0V	0.1mV/0.001V/0.01V//0.1V
Frequency	60.00Hz/600.0Hz/6.000kHz/60.00kHz /600.0kHz/6.000MHz/60.00MHz	0.01Hz/0.1Hz/0.001kHz/0.01kHz /0.1kHz/0.001MHz/0.01MHz
Duty Ratio	1-99%	0.1%
Resistance	600.0Ω/6.000kΩ/60.00kΩ/600.0kΩ /6.000MΩ/60.00MΩ	0.1Ω/0.001kΩ/0.01kΩ/0.1kΩ /0.001MΩ/0.01MΩ
Capacitance	60.00nF/600.0nF/6.000μF/60.00 μF /600.0 μF /6.000mF/60.00mF	0.01 nF /0.1 nF /0.001 μF /0.01 μF /0.1 μF /0.001mF/0.01mF
Temperature	-20°C~1000°C(-4°F~1832°F)	1°C/ 1°F
Continuity and Diode Test		✓
VoltSense (NCV)	High Sensitivity(80V-600V) Low Sensitivity(160V-600V)	

### Product Code Information

SKU	KPSDCM450MINICBINT
EAN code	8435394788920
UPC code	810053678589
Pcs/export carton	36