

Product Environmental Profile

DOOR MOUNTING KIT FOR GRAPHIC KEYPAD






General information

Representative product	DOOR MOUNTING KIT FOR GRAPHIC KEYPAD - VW3A1112
Description of the product	Door mounting kit - for remote graphic terminal
Functional unit	This kit allow to fix a graphic display terminal on a eletrical cabinet. Calculation of the environmental impacts is based on 10 years of product service lifetime. The usage profile taken into account is 100% uptime in use phase.



Constituent materials

Reference product mass 125,9 g including the product, its packaging and additional elements and accessories



Plastics	81,6%
Metals	15,4%
Others	38,2%



Substance assessment

Products of this range are designed in conformity with the requirements of the RoHS directive (European Directive 2011/65/EU of 8 June 2011) and do not contain, or only contain in the authorised proportions, lead, mercury, cadmium, hexavalent chromium or flame retardants (polybrominated biphenyls - PBB, polybrominated diphenyl ethers - PBDE) as mentioned in the Directive

Details of ROHS and REACH substances information are available on the Schneider-Electric Green Premium website

<http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page>

Additional environmental information


The DOOR MOUNTING KIT FOR GRAPHIC KEYPAD presents the following relevant environmental aspects

Design	Indicate all the eco-design improvements brought to the product at the design phase compared to previous offer range, refer to ecoDesign Way results
Manufacturing	Manufactured at a Schneider Electric production site ISO14001 certified
Distribution	Weight and volume of the packaging optimized, based on the European Union's packaging directive Packaging weight is 54,6 g, consisting of Cardboard (62,4%), Plastic (19%), Paper (18,6%)
Installation	The product does not require any installation operation.
Use	The product does not require special maintenance operations.
End of life	End of life optimized to decrease the amount of waste and allow recovery of the product components and materials No special end-of-life treatment required. According to countries' practices this product can enter the usual end-of-life treatment process. Recyclability potential: 2% Based on "ECO'DEEE recyclability and recoverability calculation method" (version V1, 20 Sep. 2008 presented to the French Agency for Environment and Energy Management: ADEME).

Environmental impacts

Reference life time	10 years			
Product category	Other equipments - Passive product - continuous operation			
Installation elements	The disposal of the packaging materials are accounted for during the installation phase (including transport to disposal).			
Use scenario	This product consumes 0W 100% of the time during 10 years.			
Geographical representativeness	Europe			
Technological representativeness	Door mounting kit - for remote graphic terminal			
Energy model used	Manufacturing	Installation	Use	End of life
	Energy model used: China	Electricity grid mix; AC; consumption mix, at consumer; < 1kV; EU-27	Electricity grid mix; AC; consumption mix, at consumer; < 1kV; EU-27	Electricity grid mix; AC; consumption mix, at consumer; < 1kV; EU-27

Compulsory indicators		DOOR MOUNTING KIT FOR GRAPHIC KEYPAD - VW3A1112					
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Contribution to mineral resources depletion	kg Sb eq	3,68E-06	3,68E-06	6,50E-10	0*	0*	0*
Contribution to the soil and water acidification	kg SO ₂ eq	4,49E-03	4,38E-03	7,42E-05	1,40E-05	0*	2,24E-05
Contribution to water eutrophication	kg PO ₄ ³⁻ eq	2,30E-03	2,27E-03	1,71E-05	6,42E-06	0*	6,82E-06
Contribution to global warming	kg CO ₂ eq	6,76E-01	6,42E-01	1,62E-02	3,43E-03	0*	1,44E-02
Contribution to ozone layer depletion	kg CFC11 eq	3,19E-08	3,13E-08	3,29E-11	2,80E-11	0*	5,58E-10
Contribution to photochemical oxidation	kg C ₂ H ₄ eq	2,76E-04	2,68E-04	5,29E-06	1,06E-06	0*	2,27E-06
Resources use	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Net use of freshwater	m3	1,70E-01	1,70E-01	0*	0*	0*	0*
Total Primary Energy	MJ	9,07E+00	8,69E+00	2,30E-01	4,30E-02	0*	1,06E-01



Optional indicators		DOOR MOUNTING KIT FOR GRAPHIC KEYPAD - VW3A1112					
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Contribution to fossil resources depletion	MJ	7,63E+00	7,27E+00	2,28E-01	4,17E-02	0*	8,55E-02
Contribution to air pollution	m ³	4,87E+01	4,70E+01	6,91E-01	2,06E-01	0*	7,81E-01
Contribution to water pollution	m ³	1,20E+02	1,16E+02	2,67E+00	4,87E-01	0*	1,00E+00
Resources use	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Use of secondary material	kg	4,29E-02	4,29E-02	0*	0*	0*	0*
Total use of renewable primary energy resources	MJ	3,33E-01	3,32E-01	3,06E-04	2,94E-04	0*	1,16E-04
Total use of non-renewable primary energy resources	MJ	8,74E+00	8,36E+00	2,29E-01	4,27E-02	0*	1,06E-01
Use of renewable primary energy excluding renewable primary energy used as raw material	MJ	2,27E-01	2,26E-01	3,06E-04	2,94E-04	0*	1,16E-04
Use of renewable primary energy resources used as raw material	MJ	1,06E-01	1,06E-01	0*	0*	0*	0*
Use of non renewable primary energy excluding non renewable primary energy used as raw material	MJ	6,53E+00	6,15E+00	2,29E-01	4,27E-02	0*	1,06E-01
Use of non renewable primary energy resources used as raw material	MJ	2,21E+00	2,21E+00	0*	0*	0*	0*
Use of non renewable secondary fuels	MJ	0,00E+00	0*	0*	0*	0*	0*
Use of renewable secondary fuels	MJ	0,00E+00	0*	0*	0*	0*	0*
Waste categories	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Hazardous waste disposed	kg	2,67E-01	1,25E-01	0*	0*	0*	1,42E-01
Non hazardous waste disposed	kg	5,97E-01	5,88E-01	5,77E-04	8,57E-03	0*	3,23E-04
Radioactive waste disposed	kg	1,72E-04	1,71E-04	4,11E-07	3,50E-07	0*	5,27E-07
Other environmental information	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Materials for recycling	kg	5,81E-02	9,94E-03	0*	4,69E-02	0*	1,31E-03
Components for reuse	kg	0,00E+00	0*	0*	0*	0*	0*
Materials for energy recovery	kg	2,51E-03	0*	0*	0*	0*	2,51E-03
Exported Energy	MJ	1,39E-04	1,31E-05	0*	1,26E-04	0*	0*

* represents less than 0.01% of the total life cycle of the reference flow

Life cycle assessment performed with EIME version EIME v5.8.1, database version 2018-11 in compliance with ISO14044.

The manufacturing phase is the life cycle phase which has the greatest impact on the majority of environmental indicators (based on compulsory indicators).

Please note that the values given above are only valid within the context specified and cannot be used directly to draw up the environmental assessment of an installation.

<i>Registration number</i>	ENVPEP2010010_V1-EN	<i>Drafting rules</i>	PCR-ed3-EN-2015 04 02
<i>Date of issue</i>	12/2020	<i>Supplemented by</i>	PSR-0005-ed2-EN-2016 03 29
<i>Validity period</i>	5 years	<i>Information and reference documents</i>	www.pep-ecopassport.org
<i>Independent verification of the declaration and data</i>			
Internal	X	External	
<i>The elements of the present PEP cannot be compared with elements from another program.</i>			
<i>Document in compliance with ISO 14021:2016 « Environmental labels and declarations - Self-declared environmental claims (Type II environmental labelling) »</i>			

Schneider Electric Industries SAS

Country Customer Care Center
<http://www.schneider-electric.com/contact>

35, rue Joseph Monier
CS 30323
FR 92500 Rueil Malmaison
RCS Nanterre 954 503 439
Capital social 896 313 776 €

www.schneider-electric.com

ENVPEP2010010_V1-EN

Published by Schneider Electric

© 2020 - Schneider Electric – All rights reserved

12/2020