

MV-232/1-43

MV live working safety shoes

Series: MV-232/1-..

Network Application: MV



Application :

- MV live working safety shoes to protect against step voltage.
- Conform to ASTM F2413:2018 Electrical Hazard resistance 18 kV.
- Conform to EDF- RTE SERECT standard: ST HTA 70A Ind. E
- Ideal for work at height (ladder, pylon).

Features :

- Textile anti-penetration sole resistant up to 1430 N.
- PU/ nitrile sole resistant up to 300°C.
- SB: Basic requirement (innocuousness, comfort, strength, resistance to shocks hazards, compression 200 J).
- SRC: slip resistance (SRA+SRB). Anti-slip sole and resistant to hydrocarbons.
- E: Shock absorption in the heel area.
- P: Penetration resistance.
- FO: Oil resistant sole.
- WRU : Stem resistant to penetration and the water absorption.
- HRO: Heat resistant outsole 300°C.
- Smooth full grain leather. Breathable Thinsulate membrane with very good thermal insulation (quick drying).
- Safety toe cap resistant up to 240 J.

Description

Use	Outdoor
Marking	SB P HRO WRU E FO
Use	Outdoor
Dimensions	
Height	240
Width	340
Depth	130
Fonctionnalité	
Weight	1.03
Material	Cuir
Size	43
Longueur	
Length	370
Network Voltage	20 kV