


# Plexo™ Weatherproof boxes

Cat. No(s): 0 920 09/21/41



### 1. USE


Special waterproof boxes for activated fire safety devices for ERP and ERT with pre-knocked entries for cable gland or cabstop.  
 Complies with ERP regulations according to art. EL16 §1  
 Complies with standard NFS 61-932 dealing with fire safety systems including activated fire safety devices (compartmentalization, smoke extraction, etc.).  
 Cover gray color RAL 7037.  
 Red color box RAL 3000.  
 Equipped with IP 2 X terminal block for the 155 x 110 box.

### 2. RANGE

Cat. No.	Internal dimensions	Number Knock-out entries	Cover Type
0 920 09	80 x 80 x 45	7	Clip-on
0 920 21	105 x 105 x 55	7	1/4 turn closure
0 920 41	155 x 110 x 74	16 + 4	1/4 turn closure


### 3. OVERALL DIMENSIONS (mm)

Cat. No: 0 920 09




### 3. OVERALL DIMENSIONS (mm) (continued)

Cat. No: 0 920 21



Cat. No: 0 920 41



### 4. TECHNICAL CHARACTERISTICS

#### ■ 5.1 Protection index

Protection against solid bodies and liquids: IP55  
 Protection against impacts: IK 07

#### ■ 5.2 Material characteristics

Boxe : ABS  
 Cover : polypropylène for boxes 0 920 09/21  
 polycarbonate for boxes 0 920 41  
 Box cover fixing screw 0 920 21/41: polyamide  
 UV-resistant  
 Halogen-free  
 Self-extinguishing: 960° C/30 s.

#### 4. TECHNICAL CHARACTERISTICS *(continued)*

##### ■ 4.3 Climate characteristics

Storage and use temperature: -25°C to +40°C

#### 5. CLEANING

Surface cleaning with a cloth.

Do not use: acetone, tar remover, trichloroethylene.

Maintenance with the following products: Hexane, Methylated spirit, Soapy water, Diluted ammonia, Bleach diluted to 10%, Window-cleaning products, Pre-saturated wipes.

**Caution:** A preliminary test should be carried out if other specific cleaning products are to be used.

#### 6. STANDARDS AND APPROVALS

Compliance with standards of installation and manufacturing.  
Refer to e.catalogue.