



	29 V _~
	10 mA
	50/60Hz
	2x2,5 mm ²
	x = 10
	4 x (Ø 0,6 mm < < Ø 0,8 mm)
	-5°C → +45°C

4000 VA	16 A	4000 VA	16 A	4000 VA	16 A	4000 VA	16 A	4000 VA	16 A	4000 VA	16 A

- Programming Button using for assigning a physical address and download application
- Bouton de programmation pour affectation d'une adresse physique et téléchargement d'applications
- Pulsante di programmazione per assegnare un indirizzo fisico e scaricare l'applicazione
- Switching Output
- Sorties ON/OFF
- Uscite di commutazione
- Channel Selection Buttons
- Boutons de sélection des voies
- Pulsanti di selezione canali
- Manual Operation Button
- Bouton Mode manuel
- Pulsante di funzionamento manuale
- 1-10V Dimming Outputs
- Sorties variation 1-10 V
- Uscite dimmerabili 1-10V
- ON/OFF, UP/DOWN Buttons
- Boutons ON/OFF, Montée/Descente
- Pulsanti ON/OFF, SU/GIÙ
- Programming LED
- Témoin de programmation
- LED programmation
- Channel Switch Status LEDs
- Témoin d'état de commutation des voies
- LED stato commutazione di canale

